



FOGO MONTANHA

FOGO MONTANHA, SA., Rua da Cova da Areia (E.M. 605), 695, 3750-071 Aguada de Cima
Águeda- Portugal - Made in Portugal

Designation Type: C700; N° Série

Emissions (13%O ₂):			Performance:		
	Nom	Part		Nom	Part
CO :	1352 mg/m ³	-	P :	9,4 kW	-
NOx :	200 mg/m ³	-	P _W :	-	-
OGC :	80 mg/m ³	-	P _{SH} :	9,4 kW	-
PM :	40 mg/m ³	-	η :	80 %	-
			p :	12 Pa	-

EN 16510-1-2022, EN 16510-2-2:2022

Flue gas outlet temperature (Nom-Part):	287 °C
Diameter of the flue gas outlet :	180 mm
Fire safety of installation to the chimney :	T400G
Seasonal space heating efficiency (η _s) :	70 %
Energy Efficiency Index (EEI) :	106
Energy Efficiency Class :	A
The permissible maximum water operation pressure (P _W - bar):	-
Protective Insulation according to manufacturer's instructions :	40 mm
Power supply voltage (E) :	230 V
Power supply frequency (f) :	50 Hz
Maximum electric power input (W _{max}) :	30W
Mass of the appliance (m) :	109 kg
Fuel Type :	Type I, Wood logs
Operation Type :	INT - Intermittent

Minimum distances to combustible materials

Bottom d _B = 0 mm	Floor d _F = 1500 mm	Side radiation area d _L = 1500 mm
Ceiling d _C = 1500 mm	Rear d _R = 700 mm	
Front d _P = 1500 mm	Side d _S = 300 mm	
Non-Comb d _{non} = -		



Only use recommended fuels / Read and follow the manual / Shared flow prohibited